

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/7/11	C. Chen

TECHNICAL DATA

► Electrical Data

Pass Band Frequency	2000-6000MHz
Pass Band Insertion Loss	≤1.0dB
Pass Band VSWR	≤1.5:1
Stop Band Rejection	≥40dB@6800~6900MHz
	≥50dB@6900~7100MHz
	≥60dB@7100~10000MHz
Impedance	50 Ohms
Power Handling	100W(design assurance)



► Mechanical Data

Dimensions	80×13×10mm
Connectors	SMA-Female
Connectors Material	Stainless Steel
Surface Finish	Silver Plated
Body	Aluminum LF6-R
Weight	32g

► Environmental Data

Operating Temperature	-40°C~+70°C
Storage Temperature	-55°C~+85°C

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 11/07/23
ENGINEER: J. Zhu 11/07/23
APPROVED: C. Chen 11/07/23
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:
Low Pass Filter,
2000-6000MHz, Stop
Band Rejection 50dB,
100W, SMA-Female
PART No.: TLF-02000600-50S

TITAN MICROWAVE INC.
A Professional RF & Microwave Components Supplier

www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE: 1:1	SHEET: 1/1	REV: A