

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/3/18	C. Chen

## TECHNICAL DATA

### ► Electrical Data

Frequency Range	2.6~3GHz
Insertion Loss	0.5dB max
VSWR	1.3:1 max
Isolation	18dB min
Impedance	50 Ohms
Forward Power	150W
Direction	Clockwise

### ► Mechanical Data

Dimensions	25.4×28.5×15mm
Connectors	N-Female
Surface Finish	Nickel Plated
Weight	100g



### ► Environmental Data

Temperature Range	-30℃~+75℃
Storage Temperature	-50℃~+90℃



#### Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 19/03/23	TITLE: Coaxial Circulator, 2.6~3GHz, 150W, Clockwise, N-Female	 <b>成都巨人微波</b> <b>TITAN MICROWAVE INC.</b> <small>- A Professional RF &amp; Microwave Components Supplier -</small>	
ENGINEER: J. Zhu 19/03/23			
APPROVED: C. Chen 19/03/23		PART No.: TMCC-02600300-150N	 DIMENSIONS IN MILLIMETERS(mm)
TOLERANCE UNLESS OTHERWISE SPECIFIED	SIZE: A4		SCALE:
x ±0.50 [0.019"]			REV: A
.x ±0.20 [0.008"]			
.xx ±0.10 [0.004"]			
ANGLES ±1°			