

TECHNICAL DATA

► Electrical Data

Frequency Range	80~1000MHz
Insertion Loss	1.0dB max
VSWR	1.38:1 max
Isolation	20dB min
Phase Balance	±2.5°
Amplitude Balance	±1.0dB max
Power Handling	300W


► Mechanical Data

Dimensions	82×42×4.3mm
Connector Type	SMD
Surface Finish	Immersion Gold
	-Prevent surface from oxidation and scratch


► Environmental Data

Operating Temperature	-55℃~+105℃
-----------------------	------------


Pin Configuration




TOP VIEW



SIDE VIEW



BOTTOM VIEW



Configurati on	Pin 1	Pin 2	Pin 3	Pin 4
Splitter	Input	-3dB ∠θ-90°	-3dB ∠θ	Isolated
Splitter	-3dB ∠θ-90°	Input	Isolated	-3dB ∠θ
Splitter	-3dB ∠θ	Isolated	Input	-3dB ∠θ-90°
Splitter	Isolated	-3dB ∠θ	-3dB ∠θ-90°	Input
Combiner	Isolated	-3dB ∠θ-90°	-3dB ∠θ	Output
Combiner	-3dB ∠θ-90°	Isolated	Output	-3dB ∠θ
Combiner	-3dB ∠θ	Output	Isolated	-3dB ∠θ-90°
Combiner	Output	-3dB ∠θ	-3dB ∠θ-90°	Isolated

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 22/11/22
ENGINEER: J. Zhu 22/11/22
APPROVED: C. Chen 22/11/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:
SMD 3dB 90° High Power
Hybrid Coupler,
80-1000MHz, 300W

PART No.:
TMHC0540W03



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------