

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	8~12GHz
Insertion Loss	0.6dB max
VSWR	1.4:1 max
Isolation	16dB min
Forward Power	30W
Reverse Power	10W
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	8.9×15×7.8mm
Connector Type	Stripline
Material	Aluminum
Surface Finish	Nickel Plated
Weight	5g

► Environmental Data

Operating Temperature	-30℃~+75℃
Storage Temperature	-50℃~+90℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23	TITLE: Drop-in Isolator 8-12GHz, 30W	 www.titan-microwave.com		
ENGINEER: J. Zhu 16/09/23				
APPROVED: C. Chen 16/09/23		 DIMENSIONS IN MILLIMETERS(mm)		
TOLERANCE UNLESS OTHERWISE SPECIFIED				
x ±0.50 [0.019"]	PART No.: TMDI-08001200-30A	SIZE:	SCALE:	SHEET:
.x ±0.20 [0.008"]		A4		1/1
.xx ±0.10 [0.004"]				REV:
ANGLES ±1°				A