

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	3~5GHz
Insertion Loss	0.5dB max
VSWR	1.25:1 max
Isolation	18dB min
Forward Power	150W
Reverse Power	100W
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	25.4×28×15mm
Connector Type	Stripline
Material	Aluminum
Surface Finish	Nickel Plated

► Environmental Data

Operating Temperature	-10℃~+60℃
Storage Temperature	-50℃~+90℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23	TITLE: Drop-in Isolator 3-5GHz, 150W	 成都巨人微波 TITAN MICROWAVE INC. <i>- A Professional RF & Microwave Components Supplier -</i> www.titan-microwave.com			
ENGINEER: J. Zhu 16/09/23					
APPROVED: C. Chen 16/09/23					
TOLERANCE UNLESS OTHERWISE SPECIFIED					
x ±0.50 [0.019"]	PART No.: TMDI-03000500-150	 DIMENSIONS IN MILLIMETERS(mm)			
.x ±0.20 [0.008"]					
.xx ±0.10 [0.004"]					
ANGLES ±1°					
SIZE: A4		SCALE:	SHEET: 1/1	REV: A	