

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2021/3/13	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2.5~3.8GHz
Insertion Loss	0.5dB max
Isolation	18dB min
VSWR	1.35:1 max
Impedance	50 Ohms
Forward Power(CW)	150W
Reverse power	100W
Rotation	Clockwise

► Mechanical Data

Input/Output Connectors	N-Female
Material	Aluminum
Surface Treatment	Nicke Plated
Dimensions	32×44×21mm

► Environmental Data

Operating Temperature	-10℃~+60℃
Storage Temperature	-50℃~+90℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 13/03/21			TITLE: Coaxial Isolator, 2.5~3.8GHz, 150W, N-Female		 成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier -		www.titan-microwave.com	
ENGINEER: J. Zhu 13/03/21								
APPROVED: C. Chen 13/03/21								
TOLERANCE UNLESS OTHERWISE SPECIFIED			PART No.: TMCI-02500380-150N		  DIMENSIONS IN MILLIMETERS(mm)			
x ±0.50 [0.019"]								
.x ±0.20 [0.008"]								
.xx ±0.10 [0.004"]								
ANGLES ±1°								
SIZE: A4			SCALE:		SHEET: 1/1		REV: A	