

## TECHNICAL DATA

### ► Electrical Data

|                 |            |
|-----------------|------------|
| Frequency Range | 1.3~1.7GHz |
| Insertion Loss  | 0.4dB max  |
| VSWR            | 1.25:1 max |
| Isolation       | 19dB min   |
| Forward Power   | 200W(CW)   |
| Direction       | Clockwise  |
| Impedance       | 50 Ohms    |

### ► Mechanical Data

|                |                |
|----------------|----------------|
| Dimensions     | 25.4×25.4×10mm |
| Connector Type | Microstrip     |
| Material       | Aluminum       |
| Surface Finish | Nickel Plated  |

### ► Environmental Data

|                       |           |
|-----------------------|-----------|
| Operating Temperature | -30℃~+75℃ |
| Storage Temperature   | -50℃~+90℃ |



#### Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

|                                      |       |          |
|--------------------------------------|-------|----------|
| DRAWN: L. Ma 26/05/22                |       |          |
| ENGINEER: J. Zhu 26/05/22            |       |          |
| APPROVED: C. Chen 26/05/22           |       |          |
| TOLERANCE UNLESS OTHERWISE SPECIFIED |       |          |
| x                                    | ±0.50 | [0.019"] |
| .x                                   | ±0.20 | [0.008"] |
| .xx                                  | ±0.10 | [0.004"] |
| ANGLES                               | ±1°   |          |

#### TITLE:

Drop-in Circulator,  
1.3~1.7GHz,  
200W, Clockwise

#### PART No.:

TMDC-01300170-200



[www.titan-microwave.com](http://www.titan-microwave.com)



DIMENSIONS IN MILLIMETERS(mm)

|             |        |               |           |
|-------------|--------|---------------|-----------|
| SIZE:<br>A4 | SCALE: | SHEET:<br>1/1 | REV:<br>A |
|-------------|--------|---------------|-----------|