

## TECHNICAL DATA

### ► Electrical Data

|                 |               |
|-----------------|---------------|
| Frequency Range | 0.955~1.22GHz |
| Insertion Loss  | 0.4dB max     |
| VSWR            | 1.25:1 max    |
| Isolation       | 20dB min      |
| Forward Power   | 300W(CW)      |
| Direction       | Clockwise     |
| Impedance       | 50 Ohms       |

### ► Mechanical Data

|                |               |
|----------------|---------------|
| Dimensions     | 35×38×11mm    |
| Connector Type | Microstrip    |
| Material       | Aluminum      |
| Surface Finish | Nickel Plated |

### ► Environmental Data

|                       |           |
|-----------------------|-----------|
| Operating Temperature | -30℃~+75℃ |
| Storage Temperature   | -50℃~+90℃ |

| REV | DESCRIPTION OF REVISION | By     | DATE      | APPROVED |
|-----|-------------------------|--------|-----------|----------|
| A   | INITIAL RELEASE         | C. Cai | 2022/5/26 | C. Chen  |



#### Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

|                                      |       |          |
|--------------------------------------|-------|----------|
| DRAWN: L. Ma 26/05/22                |       |          |
| ENGINEER: J. Zhu 26/05/22            |       |          |
| APPROVED: C. Chen 26/05/22           |       |          |
| TOLERANCE UNLESS OTHERWISE SPECIFIED |       |          |
| x                                    | ±0.50 | [0.019"] |
| .x                                   | ±0.20 | [0.008"] |
| .xx                                  | ±0.10 | [0.004"] |
| ANGLES                               | ±1°   |          |

#### TITLE:

Drop-in Circulator,  
0.955~1.22GHz,  
300W, Clockwise

#### PART No.:

TMDC-00950122-300



[www.titan-microwave.com](http://www.titan-microwave.com)



DIMENSIONS IN MILLIMETERS(mm)

|             |        |               |           |
|-------------|--------|---------------|-----------|
| SIZE:<br>A4 | SCALE: | SHEET:<br>1/1 | REV:<br>A |
|-------------|--------|---------------|-----------|