

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	100~800MHz
Insertion Loss	≤0.7dB typ
VSWR	≤1.3:1
Isolation	≥18dB
Phase Balance	≤±4°
Amplitude Balance	≤±0.9dB
Power Handling	400W(CW)

► Mechanical Data

Dimensions	41×69.8×2.5mm
Connector Type	Stripline
Surface Finish	Immersion Gold

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22
ENGINEER: J. Zhu 16/04/22
APPROVED: C. Chen 16/04/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

SMD 90° Hybrid Coupler,
3dB, 100-800MHz,
400W

PART No.:

TM0874-3



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------