

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	250~2500MHz
Insertion Loss	0.8dB max
VSWR Primary	1.25:1 max
VSWR Secondary	1.25:1 max
Directivity	18dB min
Nominal Coupling	20±1.5dB
Frequency Sensitivity	±0.9dB typ, ±1.0dB max
Average Power	30W
Impedance	50 Ohms

► Mechanical Data

Dimensions	292×17×12.7mm
Connector Type	SMA-Female
Surface Finish	Conductive Oxidation

► Environmental Data

Operating Temperature	-45℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22
ENGINEER: J. Zhu 16/04/22
APPROVED: C. Chen 16/04/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

Single Directional Coupler,
0.25~2.5GHz, 20dB, 30W,
SMA-Female

PART No.:

TMDC-00250250-20S30



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------