

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	6000~40000MHz
Insertion Loss	1.2dB max
VSWR Primary	1.5:1 typ, 1.8:1 max
VSWR Secondary	1.5:1 typ, 1.8:1 max
Directivity	10dB min
Nominal Coupling	30±1.9dB
Frequency Sensitivity	±1.2dB max
Average Power	30W
Impedance	50 Ohms

► Mechanical Data

Dimensions	28×11×15mm
Connector Type	2.92mm-Female
Surface Finish	Black/Gray Painted

► Environmental Data

Operating Temperature	-45℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22	TITLE: Single Directional Coupler, 6~40GHz, 30dB, 30W, 2.92mm-Female	 成都巨人微波 TITAN MICROWAVE INC. <i>- A Professional RF & Microwave Components Supplier -</i>			
ENGINEER: J. Zhu 16/04/22		www.titan-microwave.com			
APPROVED: C. Chen 16/04/22					
TOLERANCE UNLESS OTHERWISE SPECIFIED					
x ±0.50 [0.019"]	PART No.: TMDC-06004000-30K30	 DIMENSIONS IN MILLIMETERS(mm)			
.x ±0.20 [0.008"]					
.xx ±0.10 [0.004"]					
ANGLES ±1°					
		SIZE: A4	SCALE:	SHEET: 1/1	REV: A