

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	800~2000MHz
Insertion Loss(average)	0.3dB max
VSWR	1.3:1 max
Isolation	18dB min
Phase Balance	±4° max
Amplitude Balance	±0.8dB max
Power Handling	300W(CW)

► Mechanical Data

Dimensions	25.4×12.7×5.3mm max
Connector Type	SMD
Surface Finish	Immersion Gold

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



INPUT	J1	J2	J3	J4
J1	-----	-3dB<0°	-3dB<-90°	Isolation
J2	-3dB<0°	-----	Isolation	-3dB<-90°
J3	-3dB<-90°	Isolation	-----	-3dB<0°
J4	Isolation	-3dB<-90°	-3dB<0°	-----

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22		
ENGINEER: J. Zhu 16/04/22		
APPROVED: C. Chen 16/04/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

SMD 90 Degree Hybrid
Coupler, 3dB, 800-
2000MHz, 300W

PART No.:

TM0193-3-300



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------