

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

Electrical Data


Frequency Range	200~2000MHz
Insertion Loss(average)	0.7dB max
VSWR	1.3:1 max
Isolation	18dB min
Phase Balance	±5° max
Amplitude Balance	±1.2dB max@200~600MHz ±1.0dB max@600~2000MHz
Power Handling	300W(CW)

Mechanical Data

Dimensions	50×28.7×3.7mm max
Connector Type	SMD
Surface Finish	Immersion Gold

Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



INPUT	J1	J2	J3	J4
J1	-----	-3dB<-90°	-3dB<0°	ISOLATION
J2	-3dB<-90°	-----	ISOLATION	-3dB<0°
J3	-3dB<0°	ISOLATION	-----	-3dB<-90°
J4	ISOLATION	-3dB<0°	-3dB<-90°	-----

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22			TITLE: SMD 90 Degree Hybrid Coupler, 3dB, 200-2000MHZ, 300W PART No.: TM010801-3-300		 成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier - www.titan-microwave.com		
ENGINEER: J. Zhu 16/04/22					 DIMENSIONS IN MILLIMETERS(mm)		
APPROVED: C. Chen 16/04/22							
TOLERANCE UNLESS OTHERWISE SPECIFIED							
x	±0.50	[0.019"]	SIZE: A4 SCALE: SHEET: 1/1 REV: A				
.x	±0.20	[0.008"]					
.xx	±0.10	[0.004"]					
ANGLES	±1°						