

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

Electrical Data


Frequency Range	100~605MHz
Insertion Loss	0.55dB max
VSWR	1.3:1 max
Isolation	18dB min
Phase Balance	±5° max
Amplitude Balance	±1.5dB max@100~200MHz ±1.1dB max@200~605MHz
Power Handling	350W(CW)

Mechanical Data

Dimensions	69.8×41×2.3mm max
Connector Type	Microstrip
Surface Finish	Natural Color Conductive Oxidation

Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22		
ENGINEER: J. Zhu 16/04/22		
APPROVED: C. Chen 16/04/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

SMD 90 Degree Hybrid
Coupler, 3dB,
100-605MHz, 350W

PART No.:

TM0188-3-350D



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------