

TECHNICAL DATA

► Electrical Data

Frequency Range	950~3050MHz
Coupling	50±1.2dB max
Insertion Loss	0.4dB max
Primary Line VSWR	1.45:1 max
Directivity	18dB min
Impedance	50 Ohms
Primary Line Power	500W(CW, max)


► Mechanical Data

Primary Line Connectors	N-Female
Coupled Connectors	SMA-Female
Housing Material	Aluminum
Surface Finish	Conductive Oxidation
Dimensions	85×44×26mm

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/8/12	C. Chen



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 12/08/23		
ENGINEER: J. Zhu 12/08/23		
APPROVED: C. Chen 12/08/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

Dual Directional Coupler,
950~3050MHz, 50dB, 500W,
N~Female &
SMA-Female

PART No.:

TDDC-00950305-50NS500



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------