

TECHNICAL DATA

► Electrical Data


Frequency Range	20~100MHz
Coupling	50±1.0dB max
Coupling Flatness	±0.8dB max
Insertion Loss	0.2dB max
Primary Line VSWR	1.15:1 max
Directivity	18dB min
Impedance	50 Ohms
Primary Line Power	600W(CW)

► Mechanical Data

Primary Line Connectors	N-Female
Coupled Connectors	SMA-Female
Housing Material	Aluminum
Surface Finish	Conductive Oxidation
Dimensions	108×44×26mm

► Environmental Data

Operating Temperature $-55^{\circ}\text{C}\sim+85^{\circ}\text{C}$



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 30/04/25		
ENGINEER: J. Zhu 30/04/25		
APPROVED: C. Chen 30/04/25		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

Dual Directional Coupler,
20~100MHz, 50dB, 600W,
N-Female & SMA-Female

PART No.:

TDDC-00020010-50NS600



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------