

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2025/4/30	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2~6GHz
Coupling	30±1.0dB
Coupling Flatness	±0.6dB max
Insertion Loss	0.3dB max
Primary Line VSWR	1.3:1 max
Coupled Line VSWR	1.5:1 max
Directivity	15dB min
Impedance	50 Ohms
Primary Line Power	250W(CW)

► Mechanical Data

Primary Line Connectors	N-Female
Coupled Connectors	SMA-Female
Housing Material	Aluminum
Surface Finish	Conductive Oxidation
Dimensions	58×28×25.4mm

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 30/04/25			TITLE: Dual Directional Coupler, 2~6GHz, 30dB, 250W, N-Female & SMA-Female	成都巨人微波 TITAN MICROWAVE INC. A Professional RF & Microwave Components Supplier - www.titan-microwave.com				
ENGINEER: J. Zhu 30/04/25				PART No.: TDDC-02000600-30NS250	DIMENSIONS IN MILLIMETERS(mm)			
APPROVED: C. Chen 30/04/25								
TOLERANCE UNLESS OTHERWISE SPECIFIED								
x	±0.50	[0.019"]		SIZE:	SCALE:	SHEET:	REV:	
.x	±0.20	[0.008"]		A4		1/1	A	
.xx	±0.10	[0.004"]						
ANGLES	±1°							