

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

Electrical Data


Frequency Range	4400~5500MHz
Insertion Loss	1.3dB max
VSWR	1.5:1 max
Isolation	18dB min
Amplitude Balance	±0.6dB max
Phase Balance	±5° max
Impedance	50 Ohms
Power Rating	50W

Mechanical Data

Input/Output Connectors	SMA-Female
Dimensions	61×42×15mm
Surface Finish	Gray Painted

Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



DRAWN: L. Ma 21/12/22		
ENGINEER: J. Zhu 21/12/22		
APPROVED: C. Chen 21/12/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:
3dB 180° Hybrid Coupler,
4400~5500MHz, 50W,
SMA-Female

PART No.:
TMHC180-04400550-50S



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
--------------------	---------------	----------------------	------------------

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY