

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2800~3200MHz
Insertion Loss	0.3dB max
VSWR	1.2:1 max
Isolation	20dB min
Average Power	200W
Load Power	20W
Pulse Power	2000W(duty cycle 25%)
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	13×13×8mm
Connector Type	Stripline
Material	Aluminum
Surface Finish	Nickel Plated

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23			TITLE: Drop-in Isolator 2800~3200MHz, Clockwise 200W	成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier - www.titan-microwave.com					
ENGINEER: J. Zhu 16/09/23				PART No.: TMDI-02800320-200	DIMENSIONS IN MILLIMETERS(mm)				
APPROVED: C. Chen 16/09/23					SIZE: A4 SCALE: SHEET: 1/1 REV: A				
TOLERANCE UNLESS OTHERWISE SPECIFIED									
x	±0.50	[0.019"]							
.x	±0.20	[0.008"]							
.xx	±0.10	[0.004"]							
ANGLES	±1°								