

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/5/26	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2600~2900MHz
Insertion Loss	0.3dB max
VSWR	1.2:1 max
Isolation	20dB min
Forward Power	200W(CW)
Pulse Power	2000W
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	16×16×7mm
Connector Type	Microstrip
Material	Aluminum
Surface Finish	Nickel Plated

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 26/05/22
ENGINEER: J. Zhu 26/05/22
APPROVED: C. Chen 26/05/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

Drop-in Circulator,
2600~2900MHz,
200W, Clockwise

PART No.:

TMDC-02600290-200



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------