

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	6000~18000MHz
Insertion Loss	1.2dB max
VSWR	1.7:1 max
Isolation	11dB min
Forward Power	50W
Pulse Power	200W(duty cycle 10%)
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	13×18.5×12mm
Connector	SMA-Female
Material	Aluminum
Surface Finish	Nickel Plated


► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23	TITLE: Coaxial Circulator 6-18GHz, 50W, SMA-Female	 成都巨人微波 TITAN MICROWAVE INC. <small>- A Professional RF & Microwave Components Supplier -</small>			
ENGINEER: J. Zhu 16/09/23				www.titan-microwave.com	
APPROVED: C. Chen 16/09/23		 DIMENSIONS IN MILLIMETERS(mm)			
TOLERANCE UNLESS OTHERWISE SPECIFIED	PART No.:		SIZE:	SCALE:	SHEET:
x ±0.50 [0.019"]	TMCC-06001800-50S	A4		1/1	A
.x ±0.20 [0.008"]					
.xx ±0.10 [0.004"]					
ANGLES ±1°					