

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/5/14	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	400~1000MHz
Insertion Loss(average)	≤0.25dB
VSWR	≤1.25:1
Isolation	≥18.5dB
Phase Balance	≤±5°
Amplitude Balance	≤±0.7dB
Power Handling	200W(CW)

► Mechanical Data

Dimensions	34.29×12.7×3.3mm
Connector Type	Drop-in
Surface Finish	Natural Color Conductive Oxidation

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



INPUT	J1	J2	J3	J4
J1	-----	-3dB<0DEG	-3dB<-90DEG	ISOLATION
J2	-3dB<0DEG	-----	ISOLATION	-3dB<-90DEG
J3	-3dB<-90DEG	ISOLATION	-----	-3dB<0DEG
J4	ISOLATION	-3dB<-90DEG	-3dB<0DEG	-----

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 14/05/22		
ENGINEER: J. Zhu 14/05/22		
APPROVED: C. Chen 14/05/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

Drop-in 90 Degree Hybrid
Coupler, 0.4-1GHz, 200W

PART No.:

TMF0174-3



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------